

**Package DYNDNS - Dynamic Update For  
Domain Name Services (DNS)  
Version 4.0.0-trunk-x86-r60807**

Tobias Gruetzmacher  
email: [fli4l@portfolio16.de](mailto:fli4l@portfolio16.de)

The fli4l-Team  
email: [team@fli4l.de](mailto:team@fli4l.de)

January 9, 2023

# Contents

<b>1. Documentation Of Package DYNDNS</b>	<b>3</b>
1.1. DYNDNS - Dynamic Update For Domain Name Services . . . . .	3
<b>A. Documentation Appendix for Package DYNDNS</b>	<b>9</b>
A.1. DYNDNS . . . . .	9
A.1.1. Adding Of New Providers . . . . .	9
A.1.2. Note Of Thanks . . . . .	10
A.1.3. Licence . . . . .	11
<b>List of Figures</b>	<b>12</b>
<b>List of Tables</b>	<b>13</b>
<b>Index</b>	<b>14</b>

# 1. Documentation Of Package DYNDNS

## 1.1. DYNDNS - Dynamic Update For Domain Name Services

This package is used to update a dynamic hostname at every dial-in process. The following services are supported:

Provider	FreeDNS (afraid.org)
DYNDNS_x_PROVIDER	AFRAID
Homepage	<a href="http://freedns.afraid.org">http://freedns.afraid.org</a>

**Important:** *Provide the last part of the URL downloadable on Afraid.org's homepage (behind the question mark) as password (Login  $\Rightarrow$  „Dynamic DNS”  $\Rightarrow$  The URL behind the Link „Direct URL”). All other informations will be ignored.*

Provider	Companity
DYNDNS_x_PROVIDER	COMPANITY
Homepage	<a href="http://www.staticip.de/">http://www.staticip.de/</a>

Provider	DDNSS
DYNDNS_x_PROVIDER	DDNSS
Homepage	<a href="http://www.ddnss.de/">http://www.ddnss.de/</a>

Provider	DHS International
DYNDNS_x_PROVIDER	DHS
Homepage	<a href="http://www.dhs.org/">http://www.dhs.org/</a>

Provider	DNS2Go
DYNDNS_x_PROVIDER	DNS2GO
Homepage	<a href="http://dns2go.com/">http://dns2go.com/</a>

Provider	DNS-O-Matic
DYNDNS_x_PROVIDER	DNSOMATIC
Homepage	<a href="http://www.dnsomatic.com">http://www.dnsomatic.com</a>

Provider	DtDNS
DYNDNS_x_PROVIDER	DTDNS
Homepage	<a href="http://www.dtdns.com/">http://www.dtdns.com/</a>

Provider	DynAccess
DYNDNS_x_PROVIDER	DYNACCESS
Homepage	<a href="http://dynaccess.de/">http://dynaccess.de/</a>

**Important:** *DynAccess offers special charges for the subdomains \*.dyn-fli4l.de, \*.dyn-fli4l.info and \*.dyn-eisfair.de because of a fli4l-DynAccess cooperation. Informations can be found here: <http://www.dyn-fli4l.de/> or <http://www.dyn-eisfair.de/>.*

## 1. Documentation Of Package DYNDNS

Provider	DynDNS.org
DYNDNS_x_PROVIDER	DYNDNS
Homepage	<a href="http://dyn.com/">http://dyn.com/</a>
Provider	DynDNS.org (custom)
DYNDNS_x_PROVIDER	DYNDNSC
Homepage	<a href="http://dyn.com/standard-dns/">http://dyn.com/standard-dns/</a>
Provider	DynDNS DK
DYNDNS_x_PROVIDER	DYNDNSDK
Homepage	<a href="http://dyndns.dk/">http://dyndns.dk/</a>
Provider	dyndns:free
DYNDNS_x_PROVIDER	DYDNDSFREE
Homepage	<a href="http://dyndnsfree.de/">http://dyndnsfree.de/</a>
Provider	eisfair.net
DYNDNS_x_PROVIDER	DYNEISFAIR
Homepage	<a href="http://www.intersales.de/it-infrastruktur/dyneisfair.html">http://www.intersales.de/it-infrastruktur/dyneisfair.html</a>

**Important:** *By using this service you support the work of the fli4l- and eisfair-developers.*

Provider	DyNS	
DYNDNS_x_PROVIDER	DYNSCX	
Homepage	<a href="http://www.dyns.cx/">http://www.dyns.cx/</a>	
Provider	GnuDIP Dynamic DNS	
DYNDNS_x_PROVIDER	GNUDIP	
Homepage	<a href="http://gnudip2.sourceforge.net/">http://gnudip2.sourceforge.net/</a>	
Provider	Provider Hurricane Electric	
DYNDNS_x_PROVIDER	HE	
Homepage	<a href="https://dns.he.net/">https://dns.he.net/</a>	
Provider	IN-Berlin e.V.	
DYNDNS_x_PROVIDER	INBERLIN	
Homepage	<a href="http://www.in-berlin.de">http://www.in-berlin.de</a>	
Provider	INWX GmbH	Co. KG
DYNDNS_x_PROVIDER	INWX	
Homepage	<a href="https://www.inwx.de/">https://www.inwx.de/</a>	
Provider	KONTENT	
DYNDNS_x_PROVIDER	KONTENT	
Homepage	<a href="http://www.kontent.de/">http://www.kontent.de/</a>	
Provider	Nerdcamp.net	
DYNDNS_x_PROVIDER	NERDCAMP	
Homepage	<a href="http://nerdcamp.net/dynamic/dns.cgi">http://nerdcamp.net/dynamic/dns.cgi</a>	
Provider	No-IP.com	
DYNDNS_x_PROVIDER	NOIP	
Homepage	<a href="http://www.no-ip.com/">http://www.no-ip.com/</a>	

## 1. Documentation Of Package DYNDNS

Provider	noxaDynDNS
DYNDNS_x_PROVIDER	NOXA
Homepage	<a href="http://www.noxa.de/">http://www.noxa.de/</a>
Provider	OVH.DE
DYNDNS_x_PROVIDER	OVHDE
Homepage	<a href="http://www.ovh.de/">http://www.ovh.de/</a>
Provider	PHPDYN
DYNDNS_x_PROVIDER	PHPDYN
Homepage	<a href="http://www.webnmail.de/phpdyn/">http://www.webnmail.de/phpdyn/</a>

**Important:** *you have to host this type for yourself*

Provider	Regfish.com
DYNDNS_x_PROVIDER	REGFISH
Homepage	<a href="http://www.regfish.de/">http://www.regfish.de/</a>
Provider	SelfHost.de
DYNDNS_x_PROVIDER	SELFHOST
Homepage	<a href="http://selfhost.de/cgi-bin/selfhost">http://selfhost.de/cgi-bin/selfhost</a>
Provider	Securepoint Dynamic DNS Service
DYNDNS_x_PROVIDER	SPDNS
Homepage	<a href="http://www.spdns.de/">http://www.spdns.de/</a>
Provider	Strato
DYNDNS_x_PROVIDER	STRATO
Homepage	<a href="http://www.strato.de/">http://www.strato.de/</a>
Provider	T-Link.de
DYNDNS_x_PROVIDER	TLINK
Homepage	<a href="http://www.t-link.de/">http://www.t-link.de/</a>
Provider	twodns.de
DYNDNS_x_PROVIDER	TWODNS
Homepage	<a href="http://www.twodns.de/">http://www.twodns.de/</a>
Provider	ZoneEdit.com
DYNDNS_x_PROVIDER	ZONEEDIT
Homepage	<a href="http://zoneedit.com/">http://zoneedit.com/</a>

We try to keep this list up-to-date but do not rely too closely on it. There is no liability at all for the correctness of this data. You may report errors or changes detected by sending a mail to the fli4l team (email: [team@fli4l.de](mailto:team@fli4l.de)).

This is a complete list. Other providers are not supported without changes. How to expand the package to support new providers can be found in the appendix.

The dynamic hostname will be actualized with every internet dial-in. The package includes a lock that prevents repeated updates of the same IP as this is frowned with some DynDNS providers and in extreme cases can lead to account blocking.

Note: The changing of the dynamic hostname may take some minutes.

## 1. Documentation Of Package DYNDNS

Before using the package you have to acquire an account with one of the providers named above. If you already have an account you are ready to start. If you have no account yet, you can be guided by the table above to find a host name which fulfills the requirements and meets the personal taste.

For the configuration you will need the following data:

- Name of the provider
- Username
- Password
- DynDNS-hostname

The Data may vary with the provider while we try to provide a consistent configuration. Sometimes the hostname equals to the username, in such cases we will try to use the Host-field and ignore the username.

**OPT\_DYNDNS** Setting this to 'yes' activates OPT\_DYNDNS.

**DYNDNS\_SAVE\_OUTPUT** By activating this with 'yes' the result of the DynDNS query will be saved to a file shown by the webserver <sup>1</sup>

**DYNDNS\_N** Change this value if you have accounts with more DynDNS providers and therefore want to update several names with every dial-in.

**DYNDNS\_x\_PROVIDER** Specify the name of the provider (see table above and hints in the config file).

**DYNDNS\_x\_USER** Your username for the DynDNS provider. Mostly an email address, a name you choose for yourself when registering or the DynDNS hostname.

**DYNDNS\_x\_PASSWORD** Your password for the DynDNS account. Be aware to keep your secret!

**DYNDNS\_x\_HOSTNAME** The *complete* DynDNS hostname for the account. Examples:

- cool.nerdcamp.net
- user.dyndns.org
- fli4luser.fli4l.net

**DYNDNS\_x\_UPDATEHOST** For the provider PHPDYN specify here on which host the updater is installed. You need this because of PHPDYN not being a real provider but only a gpl'd script actualizing a PowerDNS Server with MySQL.

**DYNDNS\_x\_CIRCUIT** Set the circuits for which dialing in should update the hostname. Circuits are separated by spaces. It may be useful to update hostnames only when dialing in via DSL. Some examples:

---

<sup>1</sup>OPT\_HTTPD

## 1. Documentation Of Package DYNDNS

```
DYNDNS_1_CIRCUIT='1 2 3'           # Only ISDN: Circuits 1 to 3
or
DYNDNS_1_CIRCUIT='pppoe'           # Only DSL: pppoe-Circuit
or
DYNDNS_1_CIRCUIT='dhcp'            # Update with DHCP providers
                                   # (opt_dhcp needed)
or
DYNDNS_1_CIRCUIT='pppoe 1'         # DSL and ISDN

or
DYNDNS_1_CIRCUIT='static'          # fli4l i.e. behind a LTE Router
```

**DYNDNS\_x\_RENEW** Some providers expect an update every n days even without your IP having changed. This interval may be set here. If no value is given an update will be forced every 29 days.

It should be noted that an update is triggered only when dialing. This means: DSL or ISDN connections or a renewing of a lease of an interface configured via DHCP like in a cable modem. If no dialing occurs for a longer time period you have to trigger the update in other ways.

### DYNDNS\_x\_EXT\_IPV4

**DYNDNS\_x\_EXT\_IPV6** This variable configures the method by which the external IP address is detected. By setting this to 'none' no external service will be queried for the IP address and the IP address of the WAN interface will be used instead. This usually works only with WAN connections which terminate directly on the fli4l, such as PPPoE via DSL. If specifying 'dyndns' the IP address used when updating is determined by using the external service of checkip.dyndns.org. When using 'stun' the list of STUN servers is queried one by one until a valid response is returned. The use of an external service to determine the IP address is necessary if the router itself is not getting the external IP. It should be noted that the router will not note a change of the external IP in this case and thus can't update the dyndns name entry immediately.

**DYNDNS\_x\_LOGIN** Some providers require the user to log in to their Web page regularly by using her/his user account to prevent the service from being deactivated. If this variable is set to 'yes', the FLI4L will do that for you. However, this only works if the dyndns package is prepared for this provider. Such a regular registration is currently only necessary and possible for the provider "DYNDNS". Please remember also that the use of this function requires OPT\_EASYCRON='yes' in package easycron.

**DYNDNS\_LOGINTIME** If you use a provider FLI4L should log into regularly to prevent deactivation of the service (see above), you can use this variable to configure at what time this login process is intended to take place. A time value in Cron format is required here, for details please read the Documentation of package easycron. The default setting is 0 8 \* \* \*, meaning a daily login at eight o'clock in the morning.

**DYNDNS\_ALLOW\_SSL** Setting this variable to 'yes' will update over an encrypted SSL connection if possible.

**DYNDNS\_LOOKUP\_NAMES** The IP should only be updated if it really changed. Many fli4l routers don't have a permanent data storage like a harddisk where this information could be saved to be present at boot time. To prevent unnecessary updates fli4l may query name servers (only in this case) for its actually registered IP. The information will be saved and used for further updates.

Note that after a reboot a new update interval will start if fli4l uses a name server to detect its IP.

**DYNDNS\_DEBUG\_PROVIDER** Setting this variable to 'yes' will record a trace of the update process for debugging purposes. Default: `DYNDNS_DEBUG_PROVIDER='no'`

**OPT\_STUN** Setting 'yes' enables the functionality for determining the external IP address via a STUN server.

**STUN\_SERVER\_N** This variable defines the number of STUN servers.

**STUN\_SERVER\_x** FQDN of the STUN server, optionally the FQDN may be expanded by the port used.

```
STUN_SERVER_1='stun.1.google.com:19302'
STUN_SERVER_2='stun1.1.google.com:19302'
STUN_SERVER_3='stun2.1.google.com:19302'
STUN_SERVER_4='stun3.1.google.com:19302'
STUN_SERVER_5='stun4.1.google.com:19302'
STUN_SERVER_6='stun01.sipphone.com'
STUN_SERVER_7='stun.ekiga.net'
STUN_SERVER_8='stun.fwdnet.net'
STUN_SERVER_9='stun.ideasip.com'
```



# A. Documentation Appendix for Package DYNDNS

## A.1. DYNDNS

### A.1.1. Adding Of New Providers

Adding new providers is easy because update-scripts are separated from provider data completely. For a new provider adapt the following files:

#### **opt/etc/dyndns/provider.NAME**

This file defines how an update is working with this provider. It mostly consists only of a list of variables but is a normal shell script that even allows complex operations to be done. This should not be necessary in most cases. These variables can be used in the file:

**\$ip** The IP of the interface that should get the dynamic hostname.

**\$host** The complete hostname the user specified in his configuration.

**\$subdom** All components of the hostname ending with the dot next to last (**name.provider.dom**)

**\$domain** the both last components of the hostname (**name.provider.dom**)

**\$provider** The symbolic name of the provider the user specified in his configuration file.

**\$user** The username for this service.

**\$pass** The password.

These variables can be put in curly brackets to be clearly distinguishable from normal text, **\$ip** i.e. becomes **\${ip}**. If using quotation marks it should be noted that within single quotes the variables mentioned above are *not* expanded while this works with double quotes. As a rule of thumb: Always use single quotes but when using variables double quotes are needed.

The following variables must be defined in this file in order to get an update working with the provider:

**provider\_update\_type** This determines the type of query sent to the provider's server. These types are supported at the moment:

**http** A predefined website of the provider will be loaded to update the DynDNS-entry.

**netcat** A predefined text will be sent to the provider's server triggering an update.

**gnudip** An update process relatively easy and secure done by two HTTP-queries.

**provider\_host** The provider's hostname that is to be contacted during an update.

**provider\_port** The port to be contacted on the provider's host. Standard-port for HTTP is 80.

Depending on the update type further variables have to be specified:

**HTTP provider\_url** The relative URL (without the hostname, but with an / at the beginning) for the provider script. For examples please have a look at the files for other providers.

**provider\_auth** (optional) If the provider needs a login via basic authentication provide the information needed here. The format is "USER:PASSWORD".

**Netcat provider\_data** The text to be sent to the provider's server. See `provider.DYNEISFAIR` as an example.

**GNUDip provider\_script** The path to the GNUDip-script on the server, mostly something like `'/cgi-bin/gdipupdt.cgi'`.

### **opt/dyndns.txt**

One or more lines for the new provider have to be inserted here. Usually a line like that is enough:

```
dyndns_%_provider    NAME    etc/dyndns/provider.NAME
```

If HTTP and Basic Authentication are used by the provider you will need the base64 executable:

```
dyndns_%_provider    NAME    files/usr/local/bin/base64
```

If other tools are needed send an email so we can validate if this is suitable for `OPT_DYNDNS`.

### **check/dyndns.exp**

In this file the provider name has to be added at the end of the long line starting with `DYNPROVIDER = ,` separated by a `'|'`.

### **doc/<Language>/tex/dyndns/dyndns\_main.tex**

Add a new paragraph to the documentation. The providers have to be sorted alphabetically by the short name given by the user in the config file. The `prov-macro` is documented at the beginning of the file, enough examples should be present.

## **A.1.2. Note Of Thanks**

At first I wish to thank Thomas Müller (email: [opt\\_dyndns@s2h.cx](mailto:opt_dyndns@s2h.cx)) who originally developed this package and maintained it for a long time. He has done exceptional work here, without him this packages would not have been possible.

I would like to thank as well Marcel Döring (email: [m@rcel.to](mailto:m@rcel.to)), who maintained the package for quite some time.

## *A. Documentation Appendix for Package DYNDNS*

A lot of people have been helping and providing ideas at the development of the package. Many thanks also to all those hard-working people.

Further thanks go to all the people contributing to the package by providing tips, new providers, bug reports and so on:

Last but not least my thanks go to Frank Meyer and the rest of the fli4l team for their tireless work to tinker with the best router in the world (;-) Please do not take this too serious).

### **A.1.3. Licence**

Copyright ©2001-2002 Thomas Müller (email: [opt\\_dyndns@s2h.cx](mailto:opt_dyndns@s2h.cx))

Copyright ©2002-2003 Tobias Gruetzmacher (email: [fli4l@portfolio16.de](mailto:fli4l@portfolio16.de))

Copyright ©2004-201x fli4l-Team (email: [team@fli4l.de](mailto:team@fli4l.de))

This program is free software. It is distributed under the terms of the GNU General Public License as provided by the Free Software Foundation. For further informations on the licence please refer to <http://www.gnu.org/licenses/gpl.txt>.

## List of Figures

## List of Tables

# Index

DYNDNS\_ALLOW\_SSL, [7](#)  
DYNDNS\_DEBUG\_PROVIDER, [8](#)  
DYNDNS\_LOGINTIME, [7](#)  
DYNDNS\_LOOKUP\_NAMES, [7](#)  
DYNDNS\_N, [6](#)  
DYNDNS\_SAVE\_OUTPUT, [6](#)  
DYNDNS\_x\_CIRCUIT, [6](#)  
DYNDNS\_x\_EXT\_IPV4, [7](#)  
DYNDNS\_x\_EXT\_IPV6, [7](#)  
DYNDNS\_x\_HOSTNAME, [6](#)  
DYNDNS\_x\_LOGIN, [7](#)  
DYNDNS\_x\_PASSWORD, [6](#)  
DYNDNS\_x\_PROVIDER, [6](#)  
DYNDNS\_x\_RENEW, [7](#)  
DYNDNS\_x\_UPDATEHOST, [6](#)  
DYNDNS\_x\_USER, [6](#)  
  
OPT\_DYNDNS, [6](#)  
OPT\_STUN, [8](#)  
  
STUN\_SERVER\_N, [8](#)  
STUN\_SERVER\_x, [8](#)